

Replacing A Polymesh Wallaby Bed

A 'HOW TO' GUIDE



Adult installation required

Read User Guide before installation

Please keep this guide for further reference

SUPER TRAMP
Part of the Family - Est 1983

Tel: +44 (0)1884 675801 | www.supertramp.co.uk | sales@jetsports.co.uk

Replacing your Rectangular Wallaby Trampoline Bed

STEP


1

First, you will need to remove your old bed from the trampoline.

Begin by removing a spring from the frame using a spring tool, then cross over to the other side of the trampoline and remove the opposite spring. Continue this process of creating a mirror image on each opposite side because this process helps to evenly distribute the tension through the bed, making the spring removal process much easier.

Use the diagram below for reference.


Remove the corner springs last.



STEP

2

Remove the packaging from your new bed and unfold it on the ground inside the trampoline frame. Make sure the painted markings are facing upwards.



TO ORDER SPARES

If you require replacement anchor straps or springs for your Boomer, these can be ordered through our website:

www.supertramp.co.uk

Wallaby Springs:
8.57 INCH (218MM)

SKU: ZZWALL5PK



Anchor Straps
SKU: PGTAS00STDBK





Kangaroo Elevator Kit
SKU: WALLELEKIT



STEP**3**

Using the diagram below as an example, begin to fit the new bed to your trampoline following the sequence 1-10.

You should continue to work at opposites at all times to evenly distribute the tension through the bed, (Example shows following the numbers within squares to eventually fitting the remaining springs until all 74 springs are attached).

**STEP****7**

Reattach the elevator kit and then the frame pads

